



# CROCVYL2 Noir 10

Heavy, precious velvet.

## Technical properties



Flame retardant



Acoustic

Applications Curtains - Decorative frames

Composition 100% FR polyester

Weight 550 g/m<sup>2</sup> 825 g/m<sup>2</sup> Width 150 cm

Fabric direction Standard Direction Fitting ↔ cm ↓ cm

Maintenance advice

Minimum order 35 linear(s) meter(s)

## Technical characteristics

|                 |                                                           |       |
|-----------------|-----------------------------------------------------------|-------|
| Flame retardant | M1 / IMO PASS                                             |       |
| Acoustic        | Noise reduction coefficient (NRC) :                       | 0.85  |
|                 | Weighted sound absorption coefficient (a <sub>w</sub> ) : | 0.90  |
|                 | Acoustic absorption class (a <sub>w</sub> ) :             | A     |
| Resilience      | Lightfastness (units Class/8)                             | 7     |
|                 | Martindale (Cycles)                                       | 60000 |
|                 | Breaking Elongation                                       |       |
|                 | Warp                                                      | 10    |
|                 | Weft                                                      | 20    |
|                 | Breaking load (daN)                                       |       |
|                 | Warp                                                      | 95    |
|                 | Weft                                                      | 100   |



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected