



OPAQ



OPAQ Blanc 01




OPAQ Océan 91




OPAQ Arctique 58




OPAQ Abricot 08




OPAQ Anthracite 38



OPAQ Sienne 29




OPAQ Perle 96




OPAQ Crème 02




OPAQ Mastic 48




OPAQ Noir 10




OPAQ BPI 00




OPAQ Beige 63




OPAQ Safran 49



OPAQ Terre 107




OPAQ Chamois 111




OPAQ Bordeaux 04




OPAQ Ecume 82



OPAQ Sapin 126



OPAQ Kaki 148





OPAQ Amande 75



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected



OPAQ Taupe 95

This plain blackout fabric has no fire rating.

Technical properties

Applications Roman blinds - Panel curtains - Lining - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 280 g/m² 784 g/m² **Width** 280 cm

Fabric direction Room high or standard direction **Fitting** ↔ cm ↓ cm

Maintenance advice ✕ ☒ ☐ ©

Minimum order 25 linear(s) meter(s)

Technical characteristics

Flame retardant	Not Classified	
Optical index	Light reflexion :	82 %
	Light absorption :	18 %
	Light transmission :	0 %
Thermal index	Solar reflexion :	74 %
	Solar absorption :	26 %
	Solar transmission :	0 %
	UV transmission :	0 %
	Gtot :	Gt 33 % Fc 55 %
Resilience	Lightfastness (units Class/8)	5
	Dimentional Stability (%)	
	Warp	-0,5
	Weft	0
	Breaking Elongation	
	Warp	26
	Weft	15
	Breaking load (daN)	
	Warp	62
	Weft	31



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected