




Cassette awning

markilux 5010

The trendy cassette awning – slim, strong and simply chic.

Product Characteristics


Wind resistance class 2
Beaufort 5 → 7.5–10.4 m/s → 28–37 km/h → 17–23 mph



1) face fixture



1) top fixture



2) shadeplus¹⁾



2) shadeplus, during extension¹⁾




3) twin steel-link chain, corrosion protected




3) bionic tendon made of high-tech fibres for optimum power transference¹⁾



4) infrared heater attached to the cassette¹⁾



5) arm connection to the front profile, decorative cap in polished chrome



6) wall sealing profile¹⁾, front profile end cap in polished chrome



1) Optional accessories

Product Characteristics

Description

- ovally shaped cassette awning in a slender design
- extremely robust construction, ideally suited for shading large areas

Special features

- option of a drop valance up to a projection of 300 cm – vertical protection against low-lying sun and inquisitive glances integrated into the front profile, can be operated manually
- option of a silentec motor – motor noise is appreciably reduced
- the awning frame colour and end cap options can be freely combined front profile end caps, decorative caps at the elbow joint and for the front profile connectors)

Dimensions

- cassette in the standard version: depth 218 mm, height 151 mm cassette with drop valance: depth 293 mm, height 151 mm (without brackets) at a projection of 300 cm
- single unit: minimum width 187 cm at the smallest projection of 150 cm, maximum width 700 cm at the largest projection of 400 cm
- also available as a coupled unit

Roller tube and lateral bearings

- round roller tube Ø 85 mm with keyway, galvanised steel – excellent stability, ensures near perfect cover performance even at the largest widths
- the cassette side caps are made of die-cast aluminium, powder coated

Awning profiles

- extruded aluminium, in façade quality, powder coated
- cassette in two parts with integrated cover profile – offering optimum protection of the awning cover against the weather
- semi-circular front profile with integrated gutter

Folding arms

- profiles in extruded aluminium, in façade quality, powder coated
- moving parts made of drop-forged aluminium – the arms are therefore extremely fracture resistant
- pivot bolts in stainless steel run in Teflon-coated bronze bushes – practically maintenance free, virtually silent and extremely hard wearing
- power transference via corrosion-protected twin steel-link chains at the elbow joint, optionally with innovative bionic tendon made of high tensile, high-tech fibres – low in friction, noiseless, insensitive to corrosion and UV resistant

End caps

- the front profile end caps are made of high-quality plastic, powder coated or with a polished chrome finish, with water drainage holes
- the decorative caps for the arm to front profile connectors are made of high-quality plastic, powder coated or with a polished chrome finish
- the decorative caps at the elbow joint are made of high-quality plastic, in black or white (depending on the awning colour) or with a polished chrome finish

Fixture brackets

- face fixture, top fixture, eaves fixture, bottom fixture
- extruded aluminium, powder coated
- pitch range 5°–35° or 36°–70°, infinitely adjustable
- spacer plates, stand-off brackets and other accessories are available

Frame and end cap colours

markilux frame colours without surcharge

traffic white, RAL 9016

metallic aluminium, RAL 9006

grey brown, similar to RAL 8019



off-white textured finish, 5233 ¹⁾

stone grey metallic, 5215 ¹⁾

anthracite metallic, 5204 ¹⁾




havana brown textured finish, 5229 ¹⁾



off-white textured finish, 5233 ¹⁾
front profile end caps in polished chrome

stone grey metallic, 5215 ¹⁾
front profile end caps in polished chrome

anthracite metallic, 5204 ¹⁾
front profile end caps in polished chrome



Combination options – possible in any frame colour.

Non-standard powder-coated finish

Bespoke frame colours incur a surcharge – matt, metallic, finely textured and pearl finishes as well as other colour ranges (DB, Tiger etc.) on request. All frame colours are available at a surcharge with enhanced corrosion protection.

Colours may differ slightly from those depicted in both hue and finish.

¹⁾ textured finish

Dimensions and configuration options

Single unit

		Awning width										Minimum width				
		250	300	350	400	450	500	550	600	650	700 ²⁾	Motor			Crank handle	
Order dimensions		187 250	251 300	301 350	351 400	401 450	451 500	501 550	551 600	601 650	651 700					
H	150	3)										200	187	—	200	187
	200	3)										250	237	—	250	237
	250	—	3)									300	287	—	300	287
	300	—	—	3)					4)	4)		350	337	—	350	337
	350 ¹⁾	—	—	—	3)					2) 3)		400	387	644	400	387
	400 ^{1) 2)}	—	—	—	—	3)			—	—	3)	450	437	694	—	—

dimensions in cm

1) = drop valance not available

2) = only available with motor drive (surcharge)

3) = please note the minimum widths!

4) = In the case of shadeplus (on request): 3 folding arms,
4 brackets, 2 rolltex bearings (surcharge)

H = projection

 = 2 folding arms
2 brackets = 2 folding arms
3 brackets = 2 folding arms, 3 brackets
1 rolltex bearing = 3 folding arms, 4 brackets
2 rolltex bearing = 2 standard arms = 2 bespoke arms (surcharge) = 3 standard arms

Operation

	standard	optional
crank handle	✓	—
spring-assisted crank handle	—	✓
hard-wired motor	—	✓
silentec motor (optionally with an external io / RTS receiver) ¹⁾	—	✓
radio-controlled motor io, 868 MHz	—	✓
radio-controlled motor RTS, 433 MHz	—	✓
868 MHz radio-controlled motor io with manual override ¹⁾	—	✓

1) For awnings with a maximum of 2 arms

Coupled awning (motor drive)¹⁾

2 fields, 1 motor, maximum width 1390 cm
3 fields, 1 motor, maximum width 1800 cm
maximum projection (depending on the width) 400 cm
junction roller
optionally with a one-piece cover (maximum of 2 fields / projection 350 cm / 15° pitch – without internal cover profile, drop valance not available)

1) N.B! Important background information can be found in the chapter “General Information”, in the section “Coupled Awnings”

Awning cover	fabric pattern no.	standard	optional
sunvas	300.. – 315..	✓	—
sunsilk	324.. / 325.. / 328.. / 369..	✓	—
sunbow	411.. - 427..	✓	—
smart art	340..	—	✓
perla FR	371.. / 372..	—	✓
valance, height 20 cm		—	✓

Drop valance^{1) 2)}

	standard	optional
height 210 cm		
maximum projection 300 cm ³⁾		
crank handle	✓	—
hard-wired motor	—	—
radio-controlled motor io, 868MHz	—	—
radio-controlled motor RTS, 433MHz	—	—
fabric pattern sunvas / sunsilk / sunbow / transolair / vuscreen Alu / Serge 600		

1) In the case of coupled awnings (2 fields) shadeplus is driven with two separate gear boxes / motor (outside left and right)

2) Only available in plain seamless fabrics (oversized, fabric width >120 cm) or in plains with a horizontal joint (fabric width 120 cm).

3) Dimensions (551–650) × 300 cm on request

Optional accessories

shadeplus, manual
folding-arm technology with bionic tendon
valance
wall sealing profile, up to a pitch of 65°
infrared heater 2500 W
infrared heater 2500 W with integrated radio-controlled receiver 868 MHz io
LED-spotline – light bar 110 × 70 mm with 5 W LED-spotlights, 180 cm / 3 spots or 300 cm / 5 spots
LED spotline io – light bar 110 × 70 mm with 5 W LED spotlights with integrated dimmable radio-controlled receiver, width 180 cm / 3 spots or 300 cm / 5 spots
automatic controls (light, wind, rain)


N.B. Important background information can be found in the chapter “Optional Accessories”

Fixture options

face fixture brackets 150 mm, 5°–35°	77921.
face fixture brackets 150 mm, 38°–65°	77936.
fixture plate A 430 × 160 × 12 mm	75328.
fixture plate B 300 × 400 × 12 mm	75327.
stand-off bracket 80–300 mm	77969.
markilux panel 250 × 230 × 49 mm	76308.
markilux panel continuous	701104
top fixture bracket 135 mm, 5°–35°	77937.
top fixture bracket 150 mm, 38°–65°	77938.
eaves fixture bracket 150 mm, 5°–35°, flat plate 150 mm	77939.
eaves fixture bracket 150 mm, 5°–35°, flat plate 270 mm	77940.
flat plate and angled bracket for eaves fixture, machine finish aluminium, 500 mm	741290
spreader plate for eaves fixture bracket 260 × 60 × 12 mm	75383.
bottom fixture 150 mm, 5°–35°	77941.

Bracket fixture range

Awning with 2 folding arms



dimensions in cm

		Awning width								
		250	300	350	400	450	500	550	600	650
Order dimensions		187	251	301	351	401	451	501	551	601
		250	300	350	400	450	500	550	600	650
		Arm position A								
H	150	172 ¹⁾	220	270	300	340	380	440	490	510
	200	222 ²⁾	223 ¹⁾	270	300	340	380	440	490	510
	250	—	272 ²⁾	273 ¹⁾	300	340	390	440	490	510
	300	—	—	322 ²⁾	323 ¹⁾	340	390	440	490	510
	350	—	—	—	372 ²⁾	373 ¹⁾	390	440	490	—
	400	—	—	—	—	422 ²⁾	423 ¹⁾	440	—	—
		BHT	No. of brackets No. of fixing points							
W	15		2 8				3 12			
BP			A 2 16 B 2 8				A 2 16 B 2 8			
DP			—				1 4			
PA			2 8				3 12			
DA / DE	13,5		2 8 2 6				3 12 3 9			

dimensions in cm

1)= coupled awnings are available in intermediate widths with a junction roller on request

2)= please note the minimum widths! Dimension **A** is only valid for standard arms! In the case of bespoke arms: **A** minus 13 cm. coupled units are not available with a junction roller

If the brackets cannot be positioned in accordance with this table, make sure the actual dimensions are noted on the order form!

The **pull-out forces** necessary for determining the correct fixing materials necessary to meet wind resistance class 2 (Beaufort 5) can be found in the password-protected dealer area of the pro.markilux.com website under "Pull-out Forces".

A = arm position

BHT = bracket width

BP = spreader plate **A** or **B**, to be positioned behind the folding arm

DA = eaves fixture brackets

DE = top fixture brackets

DP = spacer plate 71644., to be positioned behind the rolltex bearing, in the case of spreader plate **A** or **B**

H = order dimension = projection

LR = rolltex bearing

M = order dimension = awning width


MB = bracket fixture range

PA = markilux panel, fixture profile, width 250 mm

W = face fixture brackets

Bracket fixture range

Awning with 3 folding arms



Order dimensions		Awning width									
		650					700				
		601 — 650		651 — 674		675 — 700		651 — 693		694 — 700	
		Arm position									
		A	B	A	B	A	B	A	B	A	B
H	150	—	—	570	265	590	265	—	—	—	—
	200	—	—	570	240	590	240	—	—	—	—
	250	—	—	570	230	590	230	—	—	—	—
	300	566 ²⁾	230 ²⁾	570	230	590	230	—	—	—	—
	350	616 ¹⁾	225 ¹⁾	—	—	—	—	616 ¹⁾	225 ¹⁾	622	230
	400	—	—	—	—	—	—	—	—	666 ¹⁾	230 ¹⁾
BHT		No. of brackets No. of fixing points									
W	15	4 16									
BP		A 3 24 B 3 12									
DP		1 4									
PA		4 16									
DA / DE	13,5	4 16 4 12									

dimensions in cm

If the brackets cannot be positioned in accordance with this table, make sure the actual dimensions are noted on the order form!

1) = please note the minimum widths! Dimension **A** is only valid for standard arms! In the case of bespoke arms: **A** minus 13 cm, coupled units are not available with a junction roller

2) = awning only available with 3 folding arms if equipped with shadeplus / drop valance – available on request

The **pull-out forces** necessary for determining the correct fixing materials necessary to meet wind resistance class 2 (Beaufort 5) can be found in the password-protected dealer area of the pro.markilux.com website under "Pull-out Forces".

A = arm position

BHT = bracket width

BP = spreader plate **A** or **B**, to be positioned behind the folding arm

DE = top fixture brackets

DA = eaves fixture brackets

DP = spacer plate 71644., to be positioned behind the rolltex bearing, in the case of spreader plate **A** or **B**

H = order dimension = projection

LR = rolltex bearing

M = order dimension = awning width









MB = bracket fixture range


PA = markilux panel, fixture profile, width 250 mm

W = face fixture brackets

Face fixture

Fixtures, fittings and accessories

 face fixture bracket 150 mm 5°-35° 77921.	 face fixture bracket 150 mm 38°-65° 77936.	 spacer plate for face/top fixture 150 × 136 × 20 mm N.B! stack to a max. height of 200 mm 716331
 spacer plate for face fixture 150 × 136 × 12 mm 71644.	 wall sealing profile incl. brush seal by the metre 76385. and 704241.	 side plate for wall sealing profile including 2 pan-head self-tapping screws 76386. and 2 × 735611
 cover plate for spacer plate and stand-off brackets in the case of external insulation 290 × 210 × 2 mm 71841.	 reduction bolt pack 10 pcs M 16 → M 12 M 16 → M 10 M 12 → M 10 M 10 → M 10	











76385. = wall sealing profile (standard width = awning width (M); up to a maximum awning pitch of 65°)

dimensions in mm

Face fixture with spreader plate A

Fixtures, fittings and accessories

	face fixture bracket 150 mm 5°-35°		face fixture bracket 150 mm 38°-65°		spreader plate A 430 × 160 × 12 mm
77921.		77936.		75328.	
	spacer plate for face fixture 150 × 136 × 12 mm		wall sealing profile incl. brush seal by the metre		side plate for wall sealing profile including 2 pan-head self-tapping screws
71644.		76385. and 704241.		76386. and 2 × 735611	
	reduction bolt pack 10 pcs	M 16 → M 12 M 16 → M 10 M 12 → M 10 M 10 → M 10			












76385. = wall sealing profile (standard width = awning width (M); up to a maximum awning pitch of 65°)

dimensions in mm

Face fixture with spreader plate B

Fixtures, fittings and accessories

 face fixture bracket 150 mm 5°-35° 77921.	 face fixture bracket 150 mm 38°-65° 77936.	 spreader plate B 300 x 400 x 12 mm 75327.
 spacer plate for face fixture 150 x 136 x 12 mm 71644.	 wall sealing profile incl. brush seal by the metre 76385. and 704241.	 side plate for wall sealing profile including 2 pan-head self-tapping screws 76386. and 2 x 735611
 stand-off strip for wall sealing by the metre 751971	 reduction bolt pack 10 pcs M 16 → M 12 M 16 → M 10 M 12 → M 10 M 10 → M 10	




751971 = stand-off strip for wall sealing profile
76385. = wall sealing profile (standard width = awning width (M); up to a maximum awning pitch of 65°)

dimensions in mm

Face fixture using the markilux panel 250 mm wide


Fixtures, fittings and accessories



markilux panel
250 × 230 × 49 mm

with decorative profiles
and end caps


76308.



face fixture bracket
150 mm

5°-35°


77921.



face fixture bracket
150 mm

38°-65°







77936.



dimensions in mm


Face fixture with markilux panel continuous

Fixtures, fittings and accessories

 markilux panel continuous with decorative profiles and end caps 701104	 face fixture bracket 150 mm 5°-35° 77921.	 face fixture bracket 150 mm 38°-65° 77936.
 bracket wall sealing profile small 76468.	 wall sealing profile incl. brush seal by the metre 76385. and 704241.	 side plate for wall sealing profile including 2 pan-head self-tapping screws 76386. and 2 × 735611

As a **continuous fixture profile**, the markilux panel will always be supplied to order on the basis of a technical drawing prepared in the factory in accordance with the awning specification.

The technical drawing shows the fixture points and pull-out forces and must be approved in writing.




- 76385. = wall sealing profile (standard width = awning width (M); up to a maximum awning pitch of 65°)
- L = individual width, max. 7000 mm (standard L = M)
- X = number of distances between the spots by way of example

dimensions in mm


Face fixture with stand-off bracket

Fixtures, fittings and accessories




face fixture bracket
150 mm
5°-35°

77921.




face fixture bracket
150 mm
38°-65°

77936.




stand-off bracket
for face-fixture bracket
77921. und 77936.
80-300 mm
incl. insulating element

77969.






cover plate for spacer
plate and stand-off
brackets in the case of
external insulation
290 × 210 × 2 mm

71841.



reduction bolt
pack 10 pcs


M 16 → M 12 | M 16 → M 10 | M 12 → M 10 | M 10 → M 10



dimensions in mm


Top fixture

Fixtures, fittings and accessories




top fixture bracket
135 mm
5°-35°

77937.



top fixture bracket
150 mm
38°-65°


77938.



spacer plate
for face/top fixture
150 × 136 × 20 mm

N.B!
stack to a max. height of
200 mm


716331




spacer plate for face
fixture
150 × 136 × 12 mm

71644.

With top fixture bracket 135 mm 5°-35° (77937.)






With top fixture bracket 150 mm 38°-65° (77938.)




dimensions in mm

Eaves fixture


Fixtures, fittings and accessories

 eaves fixture bracket 150 mm, 5°-35° height of flat plate 150 mm 77939.	 eaves fixture bracket 150 mm, 5°-35° height of flat plate 270 mm 77940.	 angle and plate for eaves fixture machine finish height of flat plate 500 mm 741290
--	--	--

With eaves fixture bracket 150 mm (77939.)






With eaves fixture bracket 270 mm (77940.)




dimensions in mm

Eaves fixture with additional plate


Fixtures, fittings and accessories

 eaves fixture bracket 150 mm, 5°-35° height of flat plate 150 mm 77939.	 eaves fixture bracket 150 mm, 5°-35° height of flat plate 270 mm 77940.	 supplementary flat plate for eaves fixture 260 × 60 × 12 mm 75383.
--	--	---

With eaves fixture bracket 150 mm (77939.)




With eaves fixture bracket 270 mm (77940.)



dimensions in mm


Bottom fixture

Fixtures, fittings and accessories




bottom fixture
150 mm, 5°–35°

77941.



reduction bolt
pack 10 pcs


M 16 → M 12 | M 16 → M 10 | M 12 → M 10 | M 10 → M 10




dimensions in mm

Awning with shadeplus

Face fixture



Top fixture




76385. = wall sealing profile (standard width = awning width (M); up to a maximum awning pitch of 65°)


dimensions in mm

Face fixture, manual operation, Gearbox eye positions

Dimensions at pitches between 5°–35°



Dimensions at pitches between 38°–65°




77921. = face fixture brackets 150 mm, 5°–35°
77936. = face fixture brackets 150 mm, 38°–65°

dimensions in mm


Top fixture, motor operation

Dimensions at pitches between 38°–65°



Top fixture, motor operation


Dimensions at pitches between 38°–65°




76385. = wall sealing profile (standard width = awning width (M); up to a maximum awning pitch of 65°)

dimensions in mm

Motor cable exit point



Face fixture, radio-controlled motor with manual override



dimensions in mm